

SOLERO II



20503LEDD-BS/ACR

LED Flush Mount

Brushed Steel Finish

Acrylic Lens

18.5"DIA. x 4"H

1 x 30 W SSL Dedicated LED (Included)

2100 Nom. Lumens


3000K, 90 CRI, 120v

Dimmable

Damp Location

ETL (US/Canada) Listed

Energy Efficient, JA8-2016/Title 24



SOLERO II



20502LEDD-BS/ACR

LED Flush Mount

Brushed Steel Finish

Acrylic Lens

16.5"DIA. x 4"H

1 x 26 W SSL Dedicated LED (Included)

1820 Nom. Lumens


3000K, 90 CRI, 120v

Dimmable

Damp Location

ETL (US/Canada) Listed

Energy Efficient, JA8-2016/Title 24



20501LEDD-BS/ACR

LED Flush Mount

Brushed Steel Finish

Acrylic Lens

14" DIA. x 4"H

1 x 26 W SSL Dedicated LED (Included)

1820 Nom. Lumens


3000K, 90 CRI, 120v

Dimmable

Damp Location

ETL (US/Canada) Listed

Energy Efficient, JA8-2016/Title 24



20500LEDD-BS/ACR

LED Flush Mount

Brushed Steel Finish

Acrylic Lens

12" DIA. x 3.75"H

1 x 20 W SSL Dedicated LED (Included)

1400 Nom. Lumens


3000K, 90 CRI, 120v

Dimmable

Damp Location

ETL (US/Canada) Listed

Energy Efficient, JA8-2016/Title 24



SOLERO

SOLERO is a simple and affordable solution to contemporary style. Powered with an energy efficient fluorescent GU24 bulb or LED model. SOLERO has an acrylic diffuser and is certified damp location. Five size options, with the largest a phenomenal 32" oval diameter. SOLERO is to shine, priced to please.



20464LEDD-BRZ/ACR



20465LEDD-CH/ACR

CHROME IS ONLY AVAILABLE
IN LED MODELS








20466GU-BS/ACR



20467LEDD-BRZ/ACR

Solero Flush Mount

Finish: BRZ BS CH in LEDD only	Glass: ACR	Included: SSL Boards	Certifications: Damp, Ceiling				
Model	Wattage	Base	Type	Kelvin	NomLumen	Dimensions	
20464GU-_/ACR	1lt x 13 W	GU-24	Spiral Fluorescent	2700k	900lm	3.5"(H); 12"(dia)	
20464LEDD-_/ACR	1lt x 15 W	SSL	90 CRI LED	3000k	1300lm	3.5"(H); 12"(dia)	
20465GU-_/ACR	2lt x 13 W	GU-24	Spiral Fluorescent	2700k	1800lm	4"(H); 14"(dia)	
20465LEDD-_/ACR	1lt x 20 W	SSL	90 CRI LED	3000k	1800lm	4"(H); 14"(dia)	
20466GU-_/ACR	3lt x 13 W	GU-24	Spiral Fluorescent	2700k	2700lm	4.5"(H); 18"(dia)	
20466LEDD-_/ACR	1lt x 30 W	SSL	90 CRI LED	3000k	2600lm	4.5"(H); 18"(dia)	
20467GU-_/ACR	6lt x 13 W	GU-24	Spiral Fluorescent	2700k	5440lm	6"(H); 24"(dia)	
20467LEDD-_/ACR	1lt x 35 W	SSL	90 CRI LED	3000k	3000lm	6"(H); 24"(dia)	



SOLERO
Emergency
Lighting Technology

This fixture is designed to provide lighting in the case of a power outage or natural disaster. The design elements of this fixture make it aesthetically pleasing while not compromising safety in any way.

The Emergency Light is designed to provide lighting for at least a minimum of 90 minutes.



20464LEDEM-BS/ACR






20465LEDEM-CH/ACR



20466LEDEM-CH/ACR

Solero Emergency LED Flush Mount

Finish: BS CH	Glass: ACR	Included: Battery, Test Switch, SSL Boards, 90 Minutes of Battery Minimum		Certifications: Damp, Ceiling (UL 924)		  
Model	Wattage	Base	Type	Kelvin	NomLumen	Dimensions
20464LEDEM-__/ACR	1ft x 15 W	SSL	90 CRI LED	3000k	1300lm	4.25"(H); 12"(dia)
20465LEDEM-__/ACR	1ft x 20 W	SSL	90 CRI LED	3000k	1800lm	4.75"(H); 14"(dia)
20466LEDEM-__/ACR	1ft x 30 W	SSL	90 CRI LED	3000k	2600lm	4.75"(H); 18"(dia)

SOLERO OVAL

A wonderful addition to our existing collection, the SOLERO OVAL is a grand 32 plus inches in width, 90 CRI, and available in brushed steel, chrome and bronze.



20468LEDD-CH/ACR




20468LEDD-BRZ/ACR



20468LEDD-BS/ACR

Solero Oval Flush Mount

Finish: BRZ BS CH	Glass: ACR	Included: All SSL Boards		Certifications: Damp, Ceiling			
Model	Wattage	Base	Type	Kelvin	NomLumen	Dimensions	
20468LEDD-_/ACR	11t x 48 W	SSL	90 CRI LED	3000k	4000lm	32.5"(L) x 18.25"(W)	