



Nitrogen Ball Pendants

Finish: BS	Glass: OPL	Included: Spiral Lamp, 6, 16, and 22-inch down rods; 10 feet of cord; Sloped ceiling adapter		Certifications: Dry, Ceiling			
Model	Wattage	Base	Type	Kelvin	NomLumen	Dimensions	
23950-BS/OPL	1lt x 60 W	E-26	A-19 Incandescent	2700k	800lm	8"(H); 53"(oah); 9"(dia)	
C23950BSOPLEN1118BS	1lt x 18 W	GU-24	Spiral Fluorescent	2700k	1250lm	8"(H); 53"(oah); 9"(dia)	
23951-BS/OPL	1lt x 100 W	E-26	A-19 Incandescent	2700k	1600lm	10.5"(H); 55"(oah); 11.5"(dia)	
C23951BSOPLEN1118BS	1lt x 18 W	GU-24	Spiral Fluorescent	2700k	1250lm	10.5"(H); 55"(oah); 11.5"(dia)	
23952-BS/OPL	1lt x 100 W	E-26	A-19 Incandescent	2700k	1600lm	12"(H); 57"(oah); 14"(dia)	
C23952BSOPLEN1118BS	1lt x 18 W	GU-24	Spiral Fluorescent	2700k	1250lm	12"(H); 57"(oah); 14"(dia)	